

Flexible installation with the ability to hang the unit from the ceiling or mount it on the floor.

Automatic movement of the blinds using 2 drive motors for adjustment both in horizontal and vertical direction.



The condensates pump (optional) has a water rising capacity of up to 700mm.

FLOOR - CEILING AIR CONDITIONING UNITS

Wi-Fi READY

R 32

INVERTER



Model		Indoor	SCFU - 36DAUA	SCFU - 48DAUA	SCFU - 60DAUA
		Outdoor	SOU-36UAU	SOU-48UAU	SOU-60UAU
Power supply		V~, Hz, Ph	220 - 240 / 50-60 / 1	220 - 240 / 50 & 60 / 1	220 - 240 / 50 & 60 / 1
Capacity	Cooling	Btu / h	36000 (9800 - 44300)	48000 (16241 - 56298)	55000 (16241 - 59710)
		KW	10,55 (2,9 - 13)	14,00 (4,76 - 16,50)	16,00 (4,76 - 17,5)
	Heating	Btu / h	38000 (8800 - 46000)	55000 (16309-55104)	58000 (16308 - 63122)
		KW	11,15 (2,6 - 13,5)	16,00 (4,78 - 16,15)	17,00 (4,78 - 18,50)
Electric data	Rated cooling power input	W	3,4 (0,71 - 4,71)	5,3 (1,71 - 6,7)	6,11 (1,71 - 6,8)
	Rated heating power input	W	3,45 (0,47 - 4,13)	5,5 (1,71 - 6,8)	5,90 (1,71 - 7,1)
	Rated cooling current	A	15 (3,2 - 21,5)	9,00 (1,50-15,00)	10,50 (1,50-15,00)
	Rated heating current	A	15,5 (2,43 - 18)	10,00 (1,50-15,00)	11,00 (1,50-15,00)
Performance	EER / COP	W / W	3,10 / 3,23	2,64 / 2,91	2,62 / 2,88
	SEER / SCOP	W / W	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0
	Net weight	Kg	44	44	44
	Gross weight	Kg	50	50	50
Refrigerant piping	Liquid side	mm (inch)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
	Gas side	mm (inch)	15,88 (5/8)	19,05 (3/4)	19,05 (3/4)

The company reserves the right to change the technical characteristics without notice.